



WD AV-GP

Power-saving Hard Drives

Power-conserving WD AV-GP SATA hard drives take advantage of WD GreenPower Technology™ to meet the 24x7 requirements of demanding audio and video environments. With power reduction of up to 40 percent, they deliver cool and quiet operation and reliability perfect for audio video applications such as PVRs, DVRs, set-top boxes (STBs) as well as surveillance video recording.



INTERFACE

SATA 3 Gb/s

WIDTH/HEIGHT

3.5-inch/1-inch

ROTATIONAL SPEED

IntelliPower

CAPACITIES

160 GB to 2 TB

MODEL NUMBERS

WD20EVDs WD7500AVDS
WD15EVDs WD5000AVDS
WD10EVDs WD5000AVVS
WD10EVVS WD3200AVVS

WD2500AVVS
WD1600AVVS

Note: Not all products may be available in all regions of the world.

Product Features

24x7 reliability

These drives are designed to last in always-on, streaming digital audio/video environments such as PVR/DVR, DVR recorders, and surveillance video recorders.

Reduced power consumption

With the combination of WD's IntelliSeek, IntelliPark, and IntelliPower technologies, WD has reduced power consumption by up to 40 percent compared to competitors' drives. Lower power means less heat and better reliability.

Quiet

Noise levels have been minimized to less than one sone* – virtually below the threshold of human hearing.

SilkStream™

Optimized for smooth, continuous digital video playback of up to twelve simultaneous HD streams. SilkStream is compatible with the ATA streaming command set so CE customers can use standard streaming management and error recovery options.

IntelliSeek™

Calculates optimum seek speeds to lower power consumption, noise, and vibration.

IntelliPower™

A fine-tuned balance of spin speed, transfer rate, and caching algorithms designed to deliver both significant power savings and solid performance.

IntelliPark™

Parks the recording heads off the disk surface during spin up, spin down, and when the drive is off. This ensures the recording head never touches the disk surface resulting in improved long term reliability due to less head wear, and improved non-operational shock tolerance.

Preemptive Wear Leveling (PWL)

The drive arm frequently sweeps across the disk to reduce uneven wear on the drive surface common to audio video streaming applications.

* A sone is a subjective unit of loudness as perceived by a person with normal hearing.



PUT YOUR LIFE ON IT®



WD AV-GP

Specifications ¹	2 TB	1.5 TB	1 TB	750 GB	500 GB	320 GB	250 GB	160 GB
Model numbers	WD20EVD5	WD15EVD5	WD10EVD5 WD10EVV5	WD7500AVD5	WD5000AVD5 WD5000AVV5	WD3200AVV5	WD2500AVV5	WD1600AVV5
Formatted capacity	2,000,398 MB	1,500,301 MB	1,000,204 MB	750,156 MB	500,107 MB	320,072 MB	251,059 MB	160,041 MB
User sectors per drive	3,907,029,168	2,930,277,168	1,953,525,168	1,465,149,168	976,773,168	625,142,448	490,350,672	312,581,808
Native command queuing	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
SATA latching connector	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Form factor	3.5-inch	3.5-inch	3.5-inch	3.5-inch	3.5-inch	3.5-inch	3.5-inch	3.5-inch
Performance								
Data transfer rate (max)								
Buffer to host (SATA)	3 Gb/s	3 Gb/s	3 Gb/s	3 Gb/s	3 Gb/s	3 Gb/s	3 Gb/s	3 Gb/s
Host to/from drive (sustained)	110 MB/s	110 MB/s	111 MB/s	110 MB/s	110 MB/s	80 MB/s	80 MB/s	80 MB/s
Cache (MB)	32	32	32 (WD10EVD5) 8 (WD10EVV5)	32	32 (WD5000AVD5) 8 (WD5000AVV5)	8	8	8
Average latency (ms)	4.2	4.2	4.2	4.2	4.2	4.2	4.2	4.2
Rotational speed (RPM)	IntelliPower	IntelliPower	IntelliPower	IntelliPower	IntelliPower	IntelliPower	IntelliPower	IntelliPower
Average drive ready time (sec)	14.5	14.5	14.3	14.3	14.3	8	8	8
Reliability/Data Integrity								
Load/unload cycles ²	300,000	300,000	300,000	300,000	300,000	300,000	300,000	300,000
Non-recoverable read errors per bits read	<1 in 10 ¹⁵	<1 in 10 ¹⁵	<1 in 10 ¹⁵	<1 in 10 ¹⁵	<1 in 10 ¹⁵	<1 in 10 ¹⁵	<1 in 10 ¹⁵	<1 in 10 ¹⁵
Limited warranty (years) ³	3	3	3	3	3	3	3	3
Power Management								
12VDC (A, max)	1.603	1.603	1.671	1.671	1.392	1.350	1.350	1.350
Average power requirements (W)								
Read/Write	5.9	5.9	4.9	4.9	4.1	4.7	4.7	4.7
Idle	4.9	4.9	4.2	4.2	3.7	2.3	2.3	2.3
Standby	0.7	0.7	0.4	0.4	0.8	0.8	0.8	0.8
Sleep	0.7	0.7	0.4	0.4	0.8	0.8	0.8	0.8
Environmental Specifications⁴								
Temperature (°C)								
Base casting (max)	70	70	70	70	70	70	70	70
Operating	0 to 60	0 to 60	0 to 60	0 to 60	0 to 60	0 to 60	0 to 60	0 to 60
Non-operating	-40 to 70	-40 to 70	-40 to 70	-40 to 70	-40 to 70	-40 to 70	-40 to 70	-40 to 70
Shock (Gs)								
Operating (2 ms, read/write)	30	30	30	30	30	30	30	30
Operating (2 ms, read)	65	65	65	65	65	65	65	65
Non-operating (2 ms)	250	250	300	300	350	350	350	350
Average acoustics (dBA) ⁵								
Idle mode	25	25	24	24	21	22	22	22
Quiet seek mode	26	26	25	25	22	22	22	22
Physical Dimensions								
Height (in./mm, max)	1.028/26.1	1.028/26.1	1.028/26.1	1.028/26.1	1.028/26.1	1.028/26.1	1.028/26.1	1.028/26.1
Length (in./mm, max)	5.787/147	5.787/147	5.787/147	5.787/147	5.787/147	5.787/147	5.787/147	5.787/147
Width (in./mm, ± .01 in.)	4/101.6	4/101.6	4/101.6	4/101.6	4/101.6	4/101.6	4/101.6	4/101.6
Weight (lb./kg, ± 10%)	1.61/0.73	1.61/0.73	1.32/0.60	1.32/0.60	0.97/0.44	0.99/0.45	0.99/0.45	0.99/0.45

¹ As used for storage capacity, one megabyte (MB) = one million bytes, one gigabyte (GB) = one billion bytes, and one terabyte (TB) = one trillion bytes. Total accessible capacity varies depending on operating environment. As used for buffer or cache, one megabyte (MB) = 1,048,576 bytes. As used for transfer rate or interface, megabyte per second (MB/s) = one million bytes per second, and gigabit per second (Gb/s) = one billion bits per second. Effective maximum SATA 3 Gb/s transfer rate calculated according to the Serial ATA specification published by the SATA-IO organization as of the date of this specification sheet. Visit www.sata-io.org for details.

² Controlled unload at ambient condition.

³ The term of the limited warranty may vary by region. Visit <http://support.wdc.com/warranty> for details.

⁴ No non-recoverable errors during operating tests or after non-operating tests.

⁵ Sound power level.

Western Digital, WD, the WD logo, and Put Your Life On It are registered trademarks in the U.S. and other countries; and WD GreenPower Technology, SilkStream, IntelliSeek, IntelliPower, and IntelliPark, and FIT Lab are trademarks of Western Digital Technologies, Inc. Other marks may be mentioned herein that belong to other companies. Product specifications subject to change without notice.

© 2010 Western Digital Technologies, Inc. All rights reserved.

Western Digital
20511 Lake Forest Drive
Lake Forest, California 92630
U.S.A.

2879-701250-A05 May 2010

For service and literature:

<http://support.wdc.com>
www.westerndigital.com

800.ASK.4WDC North America
800.832.4778 Spanish
+800.6008.6008 Asia Pacific
00800.27549338 Europe
(toll free where available)
+31.880062100 Europe/Middle East/Africa

